

# CS16

## Walk-Behind Micro-Scrubber

### High Productivity for Congested Areas

The CS16 is a compact, reliable, and user-friendly micro-scrubber that provides effective cleaning in tight spaces. Its easy-to-use controls, low-profile design and ergonomic handle provide easy operation. The CS16 is ideal for hard-to-reach spaces in areas such as hospitals, retail stores and offices.



### ECO Mode

Reduce noise levels and water consumption while increasing run-time with ECO mode.



### Compact Storage

Easy to operate in tight spaces and store in crowded storage rooms. Adjustable handle makes it easy to maneuver and store.



### Easy-To-Remove Recovery Tank

Keep dirty water separate from clean water with separate solution and recovery tanks. Plus easily remove tank to for battery access.

## Inside the CS16

1. **Comfortable grip and adjustable handle** for ergonomic operation.
2. **3-Stage vacuum motor** for strong water pick-up.
3. **Big capacity:**  
3.9 gal (15 L) solution tank  
4.4 gal (16.5 L) recovery tank.
4. **Parabolic squeegee shape tracks** the movement of the machine for excellent water pick-up.
5. **Brush cover** made out of durable material.
6. **Simple no-tools, no-touch brush change** system.



## CS16 Specifications

FEATURE	SPECIFICATION
Cleaning path	13.8 in / 350 mm
Productivity (per hour) Theoretical Max	13,993 ft <sup>2</sup> / 1,300 m <sup>2</sup>
Estimated coverage	10,226 ft <sup>2</sup> / 950 m <sup>2</sup>
Max speed	2.2 mph / 3.5 km/h
Brush RPM	140
Brush/pad pressure	55 lbs / 25 kg
Solution tank capacity	3.9 gal / 15 L
Recovery tank capacity	4.4 gal / 16.5 L
Run time standard   eco mode (up to hours)*	60 mins   70 mins
Power voltage	24 V
Length x width x height (handle in upright position)	37.4 x 17.7 x 47.2 in / 950 x 450 x 1,200 mm
Length x width x height (storage position with handle folded down)	37.4 x 17.7 x 26.1 in / 950 x 450 x 665 mm
Weight (without Batteries)	79.3 lbs / 36 kg
Sound level (operator's ear)**	68 dBA   66 dBA (eco mode)

Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.

\* Run times are based on Continuous Scrubbing Run Times.

\*\* For CE compliance, sound level is measured as an A-weighted sound pressure level per ISO 11201 and reported in accordance with ISO 4871.

For a demonstration or additional information,  
call **+1.800.553.8033** or email **info@tennantco.com**

**Tennant Company**

10400 Clean Street, Eden Prairie, MN 55344-2650

USA/Canada: +1.800.553.8033 | Quebec: +1.800.361.9050 | Overseas: +1.763.540.1315