



# DCM-751B\_H-OS

## OPTI-SERVE SERIES SANITARY CUBELET ICE MACHINE/DISPENSER



DCM-751BAH-OS  
03/31/17  
Item # 13291

W x D x H  
34<sup>1/16</sup>" x 28<sup>1/2</sup>" x 48<sup>1/16</sup>" \*

SD-700  
34<sup>1/4</sup>" x 28<sup>1/4</sup>" x 32<sup>1/2</sup>"

SD-750  
34" x 28" x 32<sup>3/4</sup>"

**DCM-751BAH-OS**  
Air-Cooled  
Shown with optional  
SD-750 Stand


**DCM-751BWH-OS**  
Water-Cooled


*\*Hands-free sensor designed for use  
with opaque containers.  
Not intended for outdoor use - avoid  
placement in direct sunlight.*



Item #: \_\_\_\_\_  
Project: \_\_\_\_\_  
Qty: \_\_\_\_\_  
AIA#: \_\_\_\_\_

## Features

- ▶ Durable stainless steel exterior
- ▶ Advanced CleanCycle24™ design 
- ▶ Stainless steel auger with greaseless bearing

- Up to 801 lbs. of ice production per 24 hours, with 70 lbs. \* built-in storage
- 2 second flush cycle every hour
- Easy to chew, cubelet ice
- Self-contained design reducing opportunities for cross contamination
- Flush cycle removes sediment for cleaner ice
- Protected by H-GUARD Plus Antimicrobial Agent 
- Removable air filters (Air-cooled model only)
- Dispenses ice and water
- R-404A Refrigerant


### Warranty:

3 Year Parts & Labor on entire machine.  
5 Year Parts on Compressor; air-cooled condenser coil.  
Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

\*Rated in accordance with AHRI Standard 820 (I-P)

Condenser	Model	ICE PRODUCTION		WATER USAGE		ELECTRICAL				Heat Rejection BTU/hr.	Shipping Weight	ENERGY STAR®
		Air / Water Temp Lbs. per 24 hours 70°/ 50°F 90°/ 70°F	Type of Ice (Hardness Rating)	Potable Gal. per 100 lbs. 90°/ 70°F	Condenser Gal. per 100 lbs. 90°/ 70°F	kWh Used per 100 lbs. 90°/ 70°F	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage			
Air-Cooled	DCM-751BAH-OS	801 583	Cubelet (90)	12.0	N/A	5.94	20A	7.3A	115V/60/1	9,300	345 lbs.	
Water-Cooled	DCM-751BWH-OS	782 678	Cubelet (84.1)	12.0	96	4.76	20A	7.9A	115V/60/1	7,600	345 lbs.	

## Cubelet Dimensions\*



\* approximate size in inches, image not to scale

## Operating Limits

- Ambient Temp Range 45 - 100°F
- Water Temp Range 45 - 90°F
- Water Pressure 10 - 113 PSIG
- Voltage Range 104 - 127V

## Service

- Allow 6" (15 cm) clearance at rear and sides for proper air circulation and ease of maintenance/ service should they be required. Allow 24" (61 cm) clearance at top to allow for removal of the auger
- Not intended for outdoor use - avoid placement in direct sunlight.*

## Plumbing

- Icemaker Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
  - Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent
- Water-Cooled Model (Lines Must Be Independent of Icemaker)
- Condenser Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
  - Condenser Drain/Return Line: Minimum 1/4" Nominal ID Hard Pipe (open drain system) or Copper Water Tubing (closed loop system) or Equivalent




# DCM-751B\_H-OS

OPTI-SERVE SERIES  
SANITARY CUBELET ICE MACHINE/DISPENSER




DCM-751BAH-OS  
12/20/16  
Item # 13291

FRONT VIEW




AIR-COOLED




WATER-COOLED

inch  
[mm]

SIDE VIEW




AIR-COOLED




WATER-COOLED

REAR VIEW




AIR-COOLED




WATER-COOLED

TOP VIEW



Front ↑  
AIR-COOLED



Front ↑  
WATER-COOLED