

Versatile performance and superior filtration deliver a cost-efficient cleaning solution.

The Maxxi II™ 35 delivers unprecedented cleaning flexibility. When dirt or dust is the primary issue, the Maxxi II-35 offers quality filtration and dust capture, in addition to crevice and dusting tools. Operators can also employ the Maxxi II-35 for wet applications.

Featuring a unique filter system, the Maxxi II-35 offers one solution for both wet and dry filtration. Designed with three durable components, the filter completely seals entry to the motor, protecting the motor from dust, debris, water or other liquids. Once the job is complete, the filter can be easily lifted out of the vacuum for a simple rinse, then replaced and ready for the next job in a matter of minutes.


The Maxxi II-35 wet/dry vacuum offers simple and reliable operation. The lightweight design ensures easy transportation. For enhanced performance, the Maxxi II-35 offers a variety of standard accessories, ranging from hoses and wands to squeegees and dusting tools.

- Hinge motor head lifts off for quick access to the motor.
- “Tip n’ pour” design allows for easy tank emptying.
- Rugged and powerful 1,100 Watt motor maximizes cleaning capacity in a variety of applications.
- Simple foot pedal squeegee release.
- Easy-to-install front-mount squeegee enables easy water pick-up in forward and backward directions.



Picture shown may not represent model quoted

• Standard equipment

Included accessories		Ref. no.	Min. required	CLARKE 35 120V/60 US
Hose Vacuum Cleaner				
	HOSE D32 1.9M CPL	107407308	0	•
Vac Nozzle Wet				
	FLOOR NOZZLE D32 RUBBER STRIP	107407310	0	•
Hard Floor Nozzle				
	FLOOR NOZZLE D32 BRUSH	107407311	0	•
Crevice Nozzle				
	CREVICE NOZZLE BLACK D32 204 MM	107407334	0	•
Tube				
	EXTENSION TUBE D32 - SS	107407309	0	•

Model	CLARKE 35 120V/60 US
Ref. no.	107409095

PRODUCT FEATURES

Tube holder	•
Dual filter system	•
Accessory storage	•





Versatile performance and superior filtration deliver a cost-efficient cleaning solution.

Technical specifications

CLARKE 35
120V/60 US

Cord length (ft)	50 ft (15 m)
Power supply (V)	120 V / 60 Hz
Suction power end of tube (W)	220 W
Airflow (l/sec.)	101 CFM (45 L/Sec)
Vacuum at nozzle (kPa)	72 in of H2O (20 kPa)
Sound pressure level (dB(A))	81 dB A
Tank capacity (Gal / l)	9 gal (35 L)
Wet filter area (cm ²)	163 in ² (1,051 cm ²)
Cartridge filter area (cm ²)	321 in ² (2,070 cm ²)
Hose length (m)	6 ft (1.9 m)
Length x width x height (cm)	19 x 17 x 29 in (46 x 42 x 73 cm)
Weight lbs (kg)	25 lb (11.5 kg)
Power Pmax	1,100 W
Dust bag capacity - dry	4 gal (18 L)
Hose Inlet	~1.25 in (32 mm)

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories		Ref. no.	Min. required	CLARKE 35 120V/60 US
Filter				
	CARTRIDGE FILTER	107407297	0	○
	DRYFILTER BOX 35L	107407298	0	○
	HEPA CARTRIDGE FILTER	107409006	0	○
Special Filter				
	WET FILTER	107407299	0	○
Hose Vacuum Cleaner				
	HOSE D32 1.9M CPL	107407308	0	●
Tube				
	EXTENSION TUBE D32 - SS	107407309	0	●
Vac Nozzle Wet				
	FLOOR NOZZLE D32 RUBBER STRIP	107407310	0	●
Hard Floor Nozzle				
	FLOOR NOZZLE D32 BRUSH	107407311	0	●



Versatile performance and superior filtration deliver a cost-efficient cleaning solution.

Accessories	Ref. no.	Min. required	CLARKE 35 120V/60 US
Crevice Nozzle			
CREVICE NOZZLE BLACK D32 204 MM	107407334	0	•

The logo for Clarke, featuring the word "Clarke" in a bold, red, sans-serif font with a registered trademark symbol (®) to the upper right of the letter 'e'.