

# Silverthorne Occasional Chair

## **Silverthorne Occasional Chair Dimensions:**

Overall Height:	42¾"
Overall Depth:	301/2"
Overall Width:	24"
Seat Height:	19"
Seat Depth:	19"
Seat Width:	211/4"
Arm Height:	27"
Chair Weight:	43 lbs.
Carton Weight:	54 lbs.
Weight Capacity:	350 lbs.
COM Details*:	4 yds.

### Stacking:

The Silverthorne Occasional Chair is nonstacking.

## **Cushion Details:**

Seat: 21/4" front tapering to 1", 1850FR foam Back: 11/2", 1030FR foam, 21/4" lumbar support

## Construction:

Superior strength hardwood plywood. Joints are glued and screwed. Seat decks use 8-gauge sinuous springs for support. Heavy-duty platform springs are used for the rocking mechanism.

### **Finish Details:**

A wide range of standard finishes is available. All chairs are finished in a catalyzed lacquer that enables the chair to perform very well in a commercial environment.

#### Wood Details:

Birch Hardwood Plywood.



- Fabric requirement for one chair includes the seat and backrest COM (Customer's Own Material) is not recommended because of the fees associated with international customs.
- \* The estimated fabric requirement is based on 54°W (137 cm) material. The actual amount required may vary
- depending on pattern, pattern matching, material width or use of multiple fabrics

  \* The fabric on the backrest is visible from the rear view of the chair

  \* Different fabrics on seat and backrest is possible



### **Mobility Options:**

The Silverthorne Occasional Chair is not available with casters or inline wheels.

### Floor Glides:

All chairs ship standard with white nylon floor glides with optional metal glides.

# Regulations:

All chairs are CA117-2013 and TSCA Title VI certified. Chairs pass BIFMA X5.5 Seating Standards. CA133 option is available.

## **Warranty Information:**

10-year limited warranty on the chair frame. 1-year limited warranty on the seat and backrest foam. Fabric manufacturer's warranty on fabric.

### Also Available in Silverthorne:



Silverthorne Stationary Rocker