



EMBLEM

INSTALLATION CHECKLIST

GENERAL MACHINE ENVIRONMENT

- ☐ The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- ☐ The counter accommodates the machine size and weight:
 - Dimensions: 22.0" (W) x 29.3" (H) x 23.9" (D)
 - Dry weight: 98 lb
- ☐ For under counter waste bin installation, a hole is cut in the counter in accordance with the Emblem chute kit template.
- ☐ Machine can safely be installed with minimum clearance:
 - Top: 6" – Necessary for filling the machine from the top, but it can also be refilled from the front.
 - Sides: 6" – Opening the door and accessing the lock.
 - Back: 1.75" – Electrical and water connections space.

ELECTRICAL REQUIREMENTS

Emblem Specifications	120 V / 60 HZ, 1440 W NEMA 5-15P GFCI
-----------------------	--

- ☐ Power outlet receptacle is NEMA 5-15R.
- ☐ Dedicated electrical circuit meets the Emblem power requirements.
- ☐ No extension cord or power strip on the circuit.



WATER SPECIFICATIONS

Pressure & Hardness

- ☐ Cold tap water pressure is between 20 psi and 80 psi.
- ☐ pH range is between 6 and 8.
- ☐ General hardness is between 10 and 70 mg/L.
- ☐ Machine water line is equipped with softness/filtration system and descaling device.

Water Network

- ☐ The water network provides cold, drinkable tap water.
- ☐ Dedicated 1/4" or 3/8" diameter water line.
- ☐ Easily accessible dedicated shutoff valve.

IMPORTANT: Do NOT use distilled water

