

Direct Supply® PTAC

Quality you've come to expect from Direct Supply at an affordable price

Improved Efficiency!

25° Heat Pump Threshold



Benefits

- **Peace of Mind:** 3-year limited warranty on parts and labor, plus a 5-year limited warranty on the sealed system
- **Easy to Use:** Large control panel with simple operation
- **Quiet Performance:** Tangential blower wheel with nearly silent 3-speed operation
- **Perfect Fit:** Sized to fit industry-standard wall sleeves of 16"H x 42"W x 14"D
- **Efficiency Settings:** Thermostat capability and temperature limiting help maintain temperatures and energy costs!
- **R32 Refrigerant:** Efficient R32 refrigerant helps with lower operating costs, energy bills, and sustainability.



1-800-634-7328 | Order on store.directsupply.com

Direct Supply® PTAC

Resistance Heat	7K BTU	7K BTU	9K BTU	9K BTU	12K BTU	15K BTU	15K BTU
Part #	#37G3M	#37G3P	#37G3B	#37G3Q	#37G2X	#37G2Y	#37G3C
Cooling BTU	7300/7200	7300/7200	8800/8700	8800/8700	12,000/11,800	14,700/14,500	14,700/14,500
Voltage (1 Phase, 60 Hz)	230/208	230/208	230/208	230/208	230/208	230/208	230/208
EER	13.1	13.1	12.8	12.8	11.6	10.6	10.6
Refrigerant Type	R32	R32	R32	R32	R32	R32	R32
Indoor CFM, High	346	346	390	390	404	430	430
Indoor CFM, Low	285	285	315	315	321	349	349
Cooling Watts	560/550	560/550	690/680	690/680	1030/1010	1,390/1,370	1,390/1,370
Current (Amps)	15	20	15	20	20	20	30
Corrosion Protection	Standard						
Manufacturer's Warranty	3 Years Parts & Labor, 5 Years Sealed System						
Dimensions	16"H x 42"W x 20% ^o "D						
Net Weight (lbs.)	98.1	98.1	101.4	101.4	108.0	105.8	105.8

Heat Pump	7K BTU	7K BTU	9K BTU	9K BTU	9K BTU	12K BTU	12K BTU	12K BTU	15K BTU	15K BTU
Part #	#37G3G	#37G3H	#37G2W	#37G3J	#37G3K	#37G3D	#37G2R	#37G2T	#37G3F	#37G2V
Cooling BTU	7200/7100	7200/7100	9200/9100	9200/9100	9,000	12,000	12000/11800	12000/11800	14,700/14,500	14,700/14,500
Reverse Heating BTU	480/460	6,200/6,000	7,800/7,500	7,800/7,500	8,000	10,800	10800/10500	10800/10500	13,500/13,200	13,500/13,200
Voltage (1 Phase, 60 Hz)	230/208	230/208	230/208	230/208	265	265	230/208	230/208	230/208	230/208
EER	13.1	13.1	12.8	12.8	11.3	10.5	11.6	11.6	10.6	10.6
COP	3.6	3.6	3.8	3.8	3.3	3.2	3.4	3.4	3.2	3.2
Refrigerant Type	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
Indoor CFM, High	355	355	424	424	388	434	435	435	416	416
Indoor CFM, Low	295	295	342	342	328	352	353	353	330	330
Cooling Watts	550/540	550/540	720/710	720/710	770	1,130	1030/1010	1030/1010	1,390/1,370	1,390/1,370
Current (Amps)	15	20	15	20	20	20	20	30	20	30
Reverse Heat (Amps)	2.6/2.7	2.6/2.7	3.4/3.6	3.4/3.6	2.90	5.1	4.8/5.1	4.8/5.1	6.5/7.4	6.0/6.4
Corrosion Protection	Standard									
Manufacturer's Warranty	3 Years Parts & Labor, 5 Years Sealed System									
Dimensions	16"H x 42"W x 20% ^o "D									
Net Weight (lbs.)	101.4	101.4	104.7	104.7	99.2	105.8	110.0	110.2	113.5	113.5

Accessories

- #C9779 Foldable Wall Sleeve
- #C9780 PTAC Aluminum Grille
- #L9352 PTAC Extruded Architectural Grille, Silver
- #C9781 PTAC Extruded Architectural Grille, Brown
- #L9353 PTAC Extruded Architectural Grille, Tan
- #G4100 PTAC Fresh Air Filter
- #C9782 Drain Kit
- #C9783 Air Filter
- #F1769 Wireless Thermostat
- #L8760 Honeywell T4 Pro Programmable Thermostat



#C9781



#C9782



#F1769



#L8760

