

HEAT/COOL ROOM AIR CONDITIONERS

Electric Heat (AE093G35AX, AE123G35AX, AE183G35AX) or
Heat Pump (AH093G35AX, AH123G35AX, AH183G35AX) Models

Wise Decision.
It's an Amana® brand.



- **Electronic touch pad with remote control**
- **High energy efficiency** with models up to 10.9 CEER saving you money when compared to lower CEER models.
- **Solid bottoms on outercases** for full seal – thru-the-wall installation.
- **100% full factory run test** on all units for high reliability and dependability.
- **Ball bearing fan motors** that are reliable, start quickly and run quietly.
- **Multi-directional airflow** to allow for cooling or heating to any part of the room. Some models contain automatic 2-way air swing feature.
- **Easy access slide-out filter** (left or right side pullout) – has a permanent polypropylene filter mesh that is easy to remove and clean.
- **Hydrophilic coating on evaporator and condenser Coils** on ALL models which allows better moisture removal, increased air flow, increased heat exchange, higher efficiencies and longer compressor life than units with uncoated coils.
- **Condensate drain spouts** on ALL models to direct condensate drainage.
- **LCDI power cords** to help reduce crimping or cuts on power cords.

| Amana Models | Electric Heat Models | | | Heat Pump Models | | |
|-----------------------------------|----------------------|-----------------|-----------------|------------------|-----------------|-----------------|
| | AE093G35AX* | AE123G35AX* | AE183G35AX* | AH093G35AX* | AH123G35AX* | AH183G35AX* |
| General Features: | | | | | | |
| Voltage | 230/208 | 230/208 | 230/208 | 230/208 | 230/208 | 230/208 |
| Discharge Air | Top | Top | Side | Top | Top | Side |
| Auto Air Swing | No | No | Yes | No | No | Yes |
| Slide-out Filter | Side Pull-out | Side Pull-out | Front Pull-out | Side Pull-out | Side Pull-out | Front Pull-out |
| Approx. Chassis Wgt. | 88 lbs | 91 lbs | 132 lbs | 91 lbs | 96 lbs | 143 lbs |
| Approx. Shipping Wgt. | 108 lbs | 111 lbs | 151 lbs | 111 lbs | 116 lbs | 162 lbs |
| Cooling: | | | | | | |
| Capacity / BTUH | 9,000 / 8,700 | 11,600 / 11,200 | 17,600 / 17,200 | 9,000 / 8,700 | 11,600 / 11,200 | 17,300 / 17,000 |
| Amps | 3.7 / 4.0 | 4.5 / 4.9 | 7.1 / 7.6 | 3.9 / 4.2 | 5.1 / 5.3 | 7.3 / 7.8 |
| Watts | 820 / 790 | 1,050 / 1,020 | 1,630 / 1,590 | 910 / 880 | 1,170 / 1,130 | 1,750 / 1,720 |
| CFM | 280 | 280 | 450 | 280 | 280 | 590 |
| E.E.R. | 11.0 | 11.0 | 10.8 | 9.9 | 9.9 | 9.9 |
| C.E.E.R. | 10.9 | 10.9 | 10.7 | 9.8 | 9.8 | 9.8 |
| Dehumidification - pts/hr | 2.3 | 2.6 | 4.2 | 2.2 | 2.5 | 4.1 |
| Electric Heat: | | | | | | |
| Capacity / BTUH | 10,700 / 8,500 | 10,700 / 8,500 | 11,000 / 9,000 | 10,700 / 8,500 | 10,700 / 8,500 | 11,000 / 9,000 |
| Amps | 16.0 / 14.6 | 16.0 / 14.6 | 16.0 / 15.6 | 16.0 / 14.6 | 16.0 / 14.6 | 16.0 / 15.6 |
| Watts | 3,580 / 2,770 | 3,580 / 2,770 | 3,680 / 3,030 | 3,580 / 2,770 | 3,580 / 2,770 | 3,680 / 3,030 |
| Heat Pump: (Reverse cycle) | | | | | | |
| Capacity / BTUH | n/a | n/a | n/a | 7,500 / 7,200 | 10,200 / 9,900 | 14,300 / 14,000 |
| Amps | n/a | n/a | n/a | 3.5 / 3.8 | 5.1 / 5.3 | 6.5 / 7.0 |
| Watts | n/a | n/a | n/a | 810 / 780 | 1,150 / 1,110 | 1,520 / 1,490 |
| C.O.P | n/a | n/a | n/a | 2.8 / 2.8 | 2.6 / 2.6 | 2.8 / 2.8 |
| Thermostatic Drain Valve | n/a | n/a | n/a | Yes | Yes | Yes |
| Dimensions: | | | | | | |
| Outer case-sleeve | | | | | | |
| Height | 15 3/8" | 15 3/8" | 16 7/8" | 15 3/8" | 15 3/8" | 16 7/8" |
| Width | 22 5/8" | 22 5/8" | 26" | 22 5/8" | 22 5/8" | 26" |
| Depth | 24" | 24" | 27 3/4" | 24" | 24" | 30 1/2" |
| Depth with Front | 26 3/4" | 26 3/4" | 29 3/4" | 26 3/4" | 26 3/4" | 32 1/2" |

* All units meet or exceed 06-01-14 D.O.E. CEER Minimums

Features: (all models)

| | |
|------------------|--|
| Electrical | 4.0' LCDI power cord; Perpendicular plug; 20-amp circuit breaker |
| Agency Approval | U.L (Under Writers Laboratory) listed; USA and Canada |
| Chassis type | Slide-out for easy installation and service accessibility |
| Fan Speeds | 3 speeds, High, Medium and Low |
| Fan ONLY | Yes – High, Medium and Low speed |
| Condensate drain | Yes – condensate drain spout on the wall sleeve |
| Window kit | Yes – included |

Plug Type

Perpendicular



20 Amps
250 Volts



Call your Amana brand PTAC sales representative at **800-647-2982** for complete details.

Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operating cost, or energy efficiency rating that is available from your retailer.

www.amana-ptac.com

Our continuing commitment to quality products may mean a change in specifications without notice. © 2015 Goodman Company, L.P.
Amana is a registered trademark of Maytag Corporation or its related companies and is used under license to Goodman Company, L.P., Houston, TX, USA. All rights reserved.

CB-ARAC4 01-15