

KREA TOUCH

INSTALLATION CHECKLIST



GENERAL MACHINE ENVIRONMENT

- ☐ The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- ☐ The counter accommodates the machine size and weight:
 - Dimensions: 16.3" (W) x 33.5" (H) x 22.3" (D)
 - Dry weight: 90 lb
- ☐ For under counter waste bin installation, a hole is cut in the counter in accordance with the Krea Touch chute kit template.
- ☐ Machine can safely be installed with minimum clearance:
 - Top: 9.9" – Filling the machine from the top.
 - Sides: 6" – Opening the door and accessing the lock.
 - Back: 1.75" – Electrical and water connections space.

ELECTRICAL REQUIREMENTS

| | |
|----------------------------------|--|
| Krea Touch Specifications | 120 V / 60 HZ, 1300 W NEMA 5-15P GFCI |
|----------------------------------|--|

- ☐ Power outlet receptacle is NEMA 5-15R.
- ☐ Dedicated electrical circuit meets the Krea Touch power requirements.
- ☐ No extension cord or power strip on the circuit.



WATER SPECIFICATIONS

Pressure & Hardness

- ☐ Water pressure is between 7.3 psig and 123.3 psig (0.5 and 8.5 bar).
- ☐ pH range is between 6.5 and 7.5.
- ☐ Hardness (TDH) is between 89 PPM and 142 PPM.
- ☐ Machine water line is equipped with softness/filtration system and descaling device.

Water Network

- ☐ The water network provides cold, drinkable tap water.
- ☐ Dedicated 1/4" or 3/8" diameter water line.
- ☐ Easily accessible dedicated shutoff valve.

