

Scottsdale Overbed Light

Includes convenient lower nightlight function.

Features:

Classic bed light fixture that allows staff and residents to control the light output. The fixture is equipped with a nightlight and dual drivers to enable flexible switching. Switching options are either a 4-position switch or a wall switch field wired to the top lamp and an on/off pull switch wired to bottom lamp(s).

Construction:

The housing is die-formed from 22-gauge steel and includes standard mounting holes and wiring access.

Finish:

Housing is finished in lighting-grade white baked gloss enamel paint. Decorative frame is made from Faux Alabaster acrylic.

Diffuser:

The front diffuser is made of cast acrylic, .22" thick and is glued to upper and lower diffusers. The upper diffuser is made of clear acrylic, .11" thick and is frosted on the inside. The lower diffuser is made from white acrylic and is .09" thick. Frame is held in place by two thumbscrews from the topside.

Electrical (LED):

The unit is wired with two UL recognized LED drivers. The shorter length fixtures produce 1350 source lumens upward and 2700 down, while the longer fixtures provide 1800 source lumens upward and 3600 down. 4-position pull switch (on up, on down, on both, all off) is standard and located near the right side of the fixture. LED nightlight with on/off control pull-switch is included.

32W/3-Bulb

Electrical (Fluorescent):

The unit is wired with two UL listed electronic high-power factor instant-start ballasts for one up, one down or one up, two down T8 lamps at 120V-50/60 Hz AC operation. 4-position, 3-circuit pull switch (on up, on down, on both, all off) is standard and located toward the right end. LED nightlight and on/off pull switch are included.

Certification:

cETLus listed for damp locations and ADA compliant.

LED:

Integrated LED modules are capable of producing a total of 4050 source lumen for 38" or 5400 source lumen for 50" in 3000K CCT. Rated for 50,000 hours and 90 CRI.

Options:

4-Way Pull Switch or Wall Switch (refer to ordering information).

Lamping:

For use with 3/25 or 3/32 Watt T8 linear fluorescent lamps.

Warranty:

3000K

4-Way Pull Switch

Wall Switch

Limited warranty: This fixture is free from defects in materials and workmanship for a period of five years from date of purchase.

Specifications and dimensions subject to change without notice.

Front View	Side View
	н , <u>і</u>

LED						
Scottsdale Overbed Light	LED	Source Lumen	ССТ	Features	Dimensions	
#E0922	0014/	1050	2000/	4-Way Pull Switch	42¼"L x 5"D x 5¼"H	
#E0923	60W	1350 up/2700 down	350 up/2700 down 3000K		42¼″L X 5″D X 5¼″H	
Fluorescent						
Fluorescent Scottsdale Overbed Light	Lamping	Source Lumen	ССТ	Features	Dimensions	
	Lamping	Source Lumen	ССТ	Features 4-Way Pull Switch	Dimensions	

1800 up/3600 down

Maxwett

#90767

#90768

54¼"L x 5"D x 5¼"H

Scottsdale Overbed Light



Foot-candles are measured at 66", 69", 72" and 75" heights and 0", 12", 24", 36" and 48" away from the wall. Three measurements at each height and distance are taken for the uplight, downlight and up/downlight combination.

36" Scottsdale LED Overbed Light (UPLIGHT ONLY)

		Measuring Distance from Wall				
		0"	12"	24"	36"	48"
<u>5</u>	75"	1.5	2.4	2.7	2.7	2.5
ar ti	72"	1.5	2.4	2.7	2.7	2.5
Hei	69"	1.5	2.4	2.8	2.7	2.4
Σ_	66"	1.5	2.5	2.8	2.6	2.3

36" Scottsdale LED Overbed Light (DOWNLIGHT ONLY)

		М	Measuring Distance from Wall				
		0"	12"	24"	36"	48"	
Ð	75"	34.5	36.8	28.1	18.8	11.6	
불불	72"	41.9	47.5	31.4	19.0	11.5	
Mour Hei	69"	47.8	49.8	34.0	20.1	11.4	
Σ	66"	58.7	57.7	37.1	20.0	11.0	

36" Scottsdale LED Overbed Light (UPLIGHT & DOWNLIGHT)

		Measuring Distance from Wall				
		0"	12"	24"	36"	48"
<u>5</u>	75"	36.7	39.4	31.8	20.9	14.4
ght di	72"	42.8	45.2	33.7	21.7	14.0
hei	69"	50.0	52.3	36.7	21.8	13.8
2	66"	60.2	59.7	30.8	21.7	13.3

48" Scottsdale LED Overbed Light (UPLIGHT ONLY)

	М	Measuring Distance from Wall				
	0"	12"	24"	36"	48"	
. ∞75 "	1.6	2.8	3.2	3.2	2.9	
휟듐 72"	1.5	2.8	3.2	3.1	2.9	
_∃≣ 69"	1.5	2.8	3.2	3.1	2.9	
≥ 66"	1.5	2.7	3.1	3.1	2.8	

48" Scottsdale LED Overbed Light (DOWNLIGHT ONLY)

Measuring Distance from Wall

		0	12"	24	36"	48"	
Ð	75"	40.5	41.8	33.3	22.1	14.5	
ght ntin	72"	47.0	47.3	35.6	22.3	14.4	
Aounting Height	69"	54.4	54.5	38.8	23.3	14.2	
Σ-	66"	64.3	63.2	40.9	23.5	14.2	-

48" Scottsdale LED Overbed Light (UPLIGHT & DOWNLIGHT)

	м	Measuring Distance from Wall				
	0"	12"	24"	36"	48"	
p. 75"	42.6	44.2	36.4	25.2	17.3	
6 75 분 72"	48.5	50.7	39.4	26.3	17.2	
<u>3</u> 🗄 69"	55.7	57.4	42.6	26.3	17.0	
≥ 66"	65.4	65.7	45.6	27.3	16.9	

Maxwell Thomas

36" Scottsdale FLR 2-Bulb Overbed Light (UPLIGHT ONLY) 36" Scottsdale FLR 3-Bulb Overbed Light

		Measuring Distance from Wall					
		0"	12"	24"	36"	48"	
<u>5</u>	75"	1.9	3.3	3.8	3.8	3.6	
nting ght	72"	2.0	3.2	3.7	3.7	3.5	
Moun Heig	69"	1.9	3.2	3.6	3.4	3.1	
Σ	66"	1.9	3.2	3.5	3.4	3.0	

36" Scottsdale FLR 2-Bulb Overbed Light (DOWNLIGHT ONLY)

		м	easuring	Distanc	e from W	all
		0"	12"	24"	36"	48"
6	75"	27.3	28.8	23.0	15.9	11.0
nting ght	72"	31.9	32.3	24.3	15.9	10.6
Mour Hei	69"	36.5	38.5	26.8	16.1	10.3
Σ	66"	45.3	43.2	27.7	16.5	10.3

36" Scottsdale FLR 2-Bulb Overbed Light (UPLIGHT & DOWNLIGHT)

		Measuring Distance from Wall					
		0"	12"	24"	36"	48"	
5	75"	25.3	25.6	19.2	12.4	7.4	
unting eight	72"	29.8	29.2	20.4	12.5	7.2	
Mour	69"	34.7	34.2	22.1	12.6	6.9	
Σ	66"	42.4	41.2	25.9	12.4	6.8	

48" Scottsdale FLR 2-Bulb Overbed Light (UPLIGHT ONLY) Measuring Distance from Wall

			measuring Distance norm man						
		0"	12"	24"	36"	48"			
<u>5</u>	75"	2.5	4.1	4.6	4.7	4.3			
불불	72"	2.3	4.1	4.8	4.7	4.3			
Heig	69"	2.3	4.0	4.5	4.3	4.0			
Σ_	66"	2.2	3.9	4.2	4.2	3.9			

48" Scottsdale FLR 2-Bulb Overbed Light (DOWNLIGHT ONLY)

		Measuring Distance from Wall					
		0"	12"	24"	36"	48"	
Ð	75"	29.4	29.8	22.9	15.0	10.0	
it ti	72"	34.8	34.3	24.6	15.6	10.1	
Hei	69"	40.6	39.9	27.0	15.9	9.7	
Σ	66"	49.7	47.1	28.8	16.6	9.4	

48" Scottsdale FLR 2-Bulb Overbed Light (UPLIGHT & DOWNLIGHT)

		Measuring Distance from Wall					
		0"	12"	24"	36"	48"	
<u>5</u>	75"	33.5	34.3	28.0	20.0	14.6	
nting ght	72"	37.9	38.7	30.4	20.3	14.7	
Tei P	69"	42.8	43.9	30.9	20.9	14.1	
ŝŤ	66"	51.8	51.5	34.7	21.3	14.0	

1-800-634-7328 / maxwellthomas.com

	ocorraduic	I EII O DUID	Overbea	- ig
(UPI	IGHT ONLY)			

		Measuring Distance from Wall				
		0"	12"	24"	36"	48"
p	75"	1.9	3.3	3.8	3.8	3.6
oting	72"	2.0	3.2	3.7	3.7	3.5
Moun Hei	69"	1.9	3.2	3.6	3.4	3.1
Σ_	66"	1.9	3.2	3.5	3.4	3.0

36" Scottsdale FLR 3-Bulb Overbed Light (DOV

WNLIGHT ONLY)		
	Measuring	Distance from Wall

		Weasuring Distance nom wan				
		0"	12"	24"	36"	48"
<u>6</u>	75"	29.1	30.5	24.3	16.0	10.6
ght B	72"	32.9	34.3	25.4	16.0	9.7
loun ¹ Heig	69"	37.0	38.7	26.8	15.6	9.4
Σ-	66"	44.7	45.0	31.2	16.8	9.2

36" Scottsdale FLR 3-Bulb Overbed Light (UPLIGHT & DOWNLIGHT)

		Measuring Distance from Wall					
		0"	12"	24"	36"	48"	
57	75"	30.5	33.7	28.0	19.5	13.7	
ght di	72"	34.8	37.6	29.7	19.9	13.3	
Hei	69"	40.9	43.6	32.9	20.2	13.1	
Σ	66"	48.4	50.8	35.3	20.6	12.6	

48" Scottsdale FLR 3-Bulb Overbed Light (UPLIGHT ONLY)

		Measuring Distance from Wall					
		0"	12"	24"	36"	48"	
6	75"	2.5	4.1	4.6	4.7	4.3	
ar ti	72"	2.3	4.1	4.8	4.7	4.3	
Mour Hei	69"	2.3	4.0	4.5	4.3	4.0	
Σ_	66"	2.2	3.9	4.2	4.2	3.9	

48" Scottsdale FLR 3-Bulb Overbed Light (DOWNLIGHT ONLY)

		м	Measuring Distance from Wall					
		0"	12"	24"	36"	48"		
<u>6</u>	75"	32.4	33.7	26.8	18.2	11.9		
ar ti	72"	37.3	38.3	29.2	19.2	12.2		
Mountii Height	69"	43.8	44.9	32.3	19.8	12.0		
Σ	66"	51.3	50.9	34.9	19.2	11.5		

48" Scottsdale FLR 3-Bulb Overbed Light (UPLIGHT & DOWNLIGHT)

		Measuring Distance from Wall						
		0"	12"	24"	36"	48"		
Ð	75"	34.9	37.8	32.0	23.3	16.8		
Mounting Height	72"	40.2	43.3	34.0	23.7	16.8		
Tei o	69"	47.8	49.1	36.8	24.2	16.0		
Σ	66"	53.5	54.3	379	23.0	15.1		