



SYMBOL

INSTALLATION CHECKLIST




GENERAL MACHINE ENVIRONMENT

- ☐ The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- ☐ The counter accommodates the machine size and weight:
 - Dimensions: 17.8" (W) x 30.5" (H) x 23.9" (D)
 - Dry weight: Up to 94 lb
- ☐ For under counter waste bin installation, a hole is cut in the counter in accordance with the Symbol chute kit template.
- ☐ Machine can safely be installed with minimum clearance:
 - Top: 6" – Filling the machine from the top.
 - Sides: 6" – Opening the door and access the lock.
 - Back: 1.75" – Electrical and water connections space.

ELECTRICAL REQUIREMENTS

Symbol Specifications	120 V / 60 HZ, 1440 W NEMA 5-15P GFCI
-----------------------	--

- ☐ Power outlet receptacle is NEMA 5-15R.
- ☐ Dedicated electrical circuit meets the Symbol power requirements.
- ☐ No extension cord or power strip on the circuit.



WATER SPECIFICATIONS

Pressure & Hardness

- ☐ Cold tap water pressure is between 20 psi and 80 psi.
- ☐ pH range is between 6 and 8.
- ☐ General hardness is between 10 and 70 mg/L.
- ☐ Machine water line is equipped with softness/filtration system and descaling device.

Water Network

- ☐ The water network provides cold, drinkable tap water.
- ☐ Dedicated 1/4" or 3/8" diameter water line.
- ☐ Easily accessible dedicated shutoff valve.

IMPORTANT: Do NOT use distilled water



Evoca North America
2355, avenue Dalton, Québec (Québec) G1P 3S3, Canada
T: 800-561-6162 - F: 800-463-2739
www.evocagroupna.com

Evoca Group Headquarters
Via Roma, 24, 24030 Valbrembo BG Italie
T: +39 035606111 - F: +39 095606560
www.evocagroup.com